

25W 2'x2' LED Troffer Light for Commercial Spaces

PRODUCT OVERVIEW

25W 2'x2' LED Troffer Light for Commercial Spaces designed for efficient, even illumination in offices, retail spaces, schools and other commercial interiors. The low-profile LED fixture provides broad 120-degree distribution with 3250lm output.

KEY PRODUCT DETAILS

3250lm	LUMINOUS FLUX
2700K / 3000K / 4100K / 5000K...	COLOR TEMPERATURE
23.54 x 23.54 x 3.34in	DIMENSIONS
CTR1025	PRODUCT CODE

PRODUCT VIEWS

25W



TECHNICAL SPECIFICATIONS

PRODUCT CODE	CTR1025
BEAM ANGLE	120 degrees
INPUT VOLTAGE	100-277VAC/50-60HZ
LUMINOUS FLUX	3250lm
DRIVER MODEL	UL Listed
POWER FACTOR	>0.95
COLOR RENDERING INDEX (CRI)	Ra > 80
POWER EFFICIENCY	>88%
LED LUMINOUS EFFICIENCY	>130.0lm/w
COLOR TEMPERATURE	2700K SW / 3000K WW / 4100K NW / 5000K DW / 5700K CW
FIXTURE MATERIAL	Precision Die Cast Aluminum Housing
APPLICATION	Offices, Lobbies, Hallways & Conference Rooms in Schools, Muni...
DIMENSIONS	23.54 x 23.54 x 3.34in

PROFESSIONAL-GRADE PRODUCTS. RELIABLE PROJECT SUPPORT.

Contact LED Lighting Solutions for availability, project pricing and technical assistance.