



24" PUSH BUTTON LED FLASHING CROSSWALK SYSTEM

- Our bright LED flashing Crosswalk Sign with push button is part of a solar traffic safety series
- This sign's bright flashing LED lights and reflective 3M material can be seen from over 2500ft and makes for a great addition for safety pertaining to reducing speed ahead
- Made with an aluminum alloy board and solar board to MUTCD (W11-2) specifications
- Sign has a rechargeable battery and mountable solar panel that makes this product energy efficient and easy to use in locations where there is sunlight

PRODUCT APPLICATIONS

Solar Powered Flashing LED Crosswalk Sign with a Push Button is used to allow pedestrians to cross the street in locations where needed

INCLUDES:

- SIGN
- SOLAR PANEL
- MOUNTING HARDWARE
- INTERNAL BATTERY BACKUP

DOES NOT INCLUDE POLE

PRODUCT SPECIFICATIONS

- TYPE:** Solar LED Traffic Safety Sign
- MUTCD:** W11-2 Pedestrian Crossing Sign
- PRODUCT CODE:** CCRS001-24-P
- SOLAR CHARGING PANEL:** 12V, 5w Monocrystalline silicone
- LED COLOR RANGE:** Yellow
- SIGN COLOR:** Engineer grade yellow
- Option: Fluorescent Yellow/ Green (only in diamond grade)
- WORKING MODE:** Push Button activation (Alternative Option: See: CCRS001-24-M)
- Wireless radio communication between signs
- WORKING TIME:** Stops 45 seconds after motion ends
- BATTERY:** Lithium battery 7.4V/4400AH
- VISIBLE DISTANCE:** >2500 feet
- WORKING TIME:** After one full charge, 5-7 consecutive days
- DIMENSIONS:** 24-inch Diamond (24"x24")
- Packing dimensions: Multi Box Shipment
- BATTERY LIFE SPAN:** 3-5 Years



*See page 6-10 for symbol design.

	A	B	C	D	E
	18	.375	.625	8	1.5
	24	.375	.625	11	1.5
C	30	.5	.75	13.5	1.875
	36	.625	.875	16	2.25
	48	.75	1.25	22	3

COLORS: SYMBOL — BLACK
BACKGROUND — YELLOW (RETROREFLECTIVE)

MUTCD GUIDELINES

The CCRS001 adheres to the MUTCD Standards found within MUTCD Guidelines Section 2A.07 for Retroreflective and Illumination

- Illumination of a sign by Light emitting diodes (LEDs)
- Sign Element to be Illuminated: (1) Symbol or word message (2) Portions of the Sign border
- LED's are placed within 1 border unit of border and within words
- LED's are red in color
- LED's are within 1/4" in width
- LED's flashing at a rate of 50 times per minute
- Background of sign is standard 3M reflective engineering grade material