



### PRODUCT APPLICATIONS

Our Solar LED Flashing Speed Limit Sign (MPH) is a bright and energy efficient traffic sign that is built for durability and will increase driver awareness wherever it is placed!

# 25MPH FLASHING SPEED LIMIT SIGN

- Our bright LED flashing Speed Limit Sign is part of a solar traffic safety series
- This sign's bright flashing LED lights and reflective 3M material can be seen from over 2500ft and makes for a great addition for safety pertaining to reducing speed ahead
- Made with an aluminum alloy board and solar board to MUTCD (R2-1) specifications
- Sign has a rechargeable battery and mountable solar panel that makes this product energy efficient and easy to use in locations where there in sunlight

#### INCLUDES:

- SIGN
- SOLAR PANEL
- MOUNTING HARDWARE
- INTERNAL BATTERY BACKUP

**DOES NOT INCLUDE POLE** 



#### **PRODUCT SPECIFICTIONS**

TYPE: 25mph Solar Traffic Safety Sign

CODE: CSPD001-025
MUTCD CODE: R2-1

SOLAR PANEL: 12V, 5W monocrystalline silicone

BATTERY: 7.4V Lithium battery 4400 AH

**BATTERY SPAN:** 3-5 years

WORKING TIME: After one full charge, 5-7 consecutive days

WORKING MODE: 24/7 or Dusk to Dawn

OPTIONAL: Timer activation (+\$100)

VISIBILE DISTANCE: >2500 feet

**DIMENSIONS:** 

PRODUCT: 18" (W) x 24" (H) inches (rectangle)

- **SHIPPING:** 26" (W) x 26" (H) x 6" (D) inches

WEIGHT: 10lbs (without junction box)

SIGN COLOR: White

LED LIGHT COLOR: White REFLECTIVE SHEETING:

STANDARD: Engineer grade reflective sheeting

OPTION: Diamond grade

**MUTCD COMPLIANT** 

OTHER SPEEDS AVAILABLE

Option: Fluorescent Yellow/ Green (only in Diamond Grade)



\*Optically space numerals about centerlin

|   | А  | В  | С    | D    | Е | F   | G | Н    | J      | K      | L    |
|---|----|----|------|------|---|-----|---|------|--------|--------|------|
| С | 18 | 24 | .375 | .625 | 3 | 3 E | 2 | 8 E  | 7.188  | 5.5    | 1.5  |
|   | 24 | 30 | .375 | .625 | 4 | 4 E | 2 | 10 E | 9.563  | 7.313  | 1.5  |
|   | 36 | 48 | .625 | .875 | 6 | 6 E | 5 | 14 E | 14.375 | 11     | 2.25 |
|   | 48 | 60 | .75  | 1.25 | 8 | 8 E | 6 | 16 E | 19.125 | 14.625 | 3    |

#### **MUTCD GUIDELINES**

## The CSPD001-025 adheres to the MUTCD Standards found within MUTCD Guidelines Section 2A.07 for Retroreflective and Illumination

- Illumination of a sign by Light emitting diodes (LEDs)
- Sign Element to be Illuminated: (1) Symbol or word message (2) Portions of the Sign border
- LED's are placed within 1 border unit of border and within words
- LED's are red in color
- LED's are within ¼" in width
- LED's flashing at a rate of 50 times per minute